

EAX[®]-500 HOW TO ORDER

EXTENDED BYPASS

0 = Alarm must be manually turned off*

NON-EXTENDED BYPASS

(When arming delay expires, if the door is open, the alarm will sound)

2 = 2 min. Auto Re-arm

3 = 10 min. Auto Re-arm

4 = 20 min. Auto Re-arm

5 = Alarm sounds if door is open after arming delay. Manual Re-arm only

EAX-5

ARMING DELAY

0 = 15 Seconds*

1 = 1 Seconds

2 = 5 Seconds

WEATHERIZED
W = Weatherized

COLOR
For standard gray,
leave blank
BK = Black

CYLINDER

If cylinder provided by others,
leave blank

MC65 = Mortise Cylinder

IC7 = 7-pin IC Cylinder Housing
(core not included)

IK7 = Cylinder InstaKey Housing
(core not included)

SIGNAGE

For standard red with white letters in English,
leave blank

RWS = Red with white letters Spanish

GWE = Green with white letters English

GWF = Green with white letters French

RWF = Red with white letters French Canadian

GWG = Green with white letters German

GWC = Green with white letters Chinese

GWE = Green with white letters German/English

SURFACE KIT

If door contact not required, leave blank

SK1 = Kit allows for wall mounting - includes
(1) MS-1039S door contact

SK2 = Kit allows for wall mounting - includes
(2) MS-1039S door contacts

SK3 = Kit allows for wall mounting - includes
(1) MS-1059S door contact

SK4 = Kit allows for wall mounting - includes
(2) MS-1059S door contacts

SK5 = Kit allows for wall mounting - includes
(1) MS-2049 door contact

SK6 = Kit allows for wall mounting - includes
(2) MS-2049 door contacts

MISCELLANEOUS

If not required, leave blank

KS = Key Stop, factory installed

STATUS INDICATOR

If status indicator not
required, leave blank

SI = Status Indicator On



Detex products can expose you to chemicals including Chromium (hexavalent compounds) and Lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.detex.com/prop65

* SK1 thru SK6 Kit Options not available in Weatherized